DEPARTMENT OF TRANSPORTATION

DIVISION OF TRANSPORTATION SOLUTIONS

Statutory Authority: 17 Delaware Code Sections 134, 141 and 21 Delaware Code Chapter 41 (17 **Del.C.** §§134,141 and 21 **Del.C.** Ch. 41)

PROPOSED

PUBLIC NOTICE

Revisions to the Delaware Manual on Uniform Traffic Control Devices, Parts 2, 3 and 6

Under Title 17 of the **Delaware Code**, Sections 134 and 141, as well as 21 **Delaware Code** Chapter 41, the Delaware Department of Transportation (DelDOT), adopted a Delaware version of the Federal Manual on Uniform Traffic Control Devices (MUTCD). The Department has now drafted revisions to Parts 2, 3, and 6 of the Delaware MUTCD. Other portions of the Delaware MUTCD, previously drafted and adopted, will likely go through a similar revision process.

DelDOT MUTCD Parts 2, 3, and 6

Figure Number/	
Table Number/	Proposed Revision
Section Number	
	Part 2
Table 2B-1	Revise to include RIGHT TURNS YIELD TO BIKES (R4-4-DE) sign.
Figure 2B-1,	
Table 2B-1, and	Revise to include ALL WAY (R1-4) plaque, previously deleted from the DelDOT MUTCD.
Section 2B.04	
Figure 2B-22,	Revise to include NOTICE MOVE OVER OR REDUCE SPEED FOR STOPPED EMERGENCY VEHICLES (SR1-18-DE) sign.
Table 2B-1, and	
Section 2B.54	
Figure 2C-9,	
	Revise to include EMERGENCY VEHICLE (W11-8-DE) warning sign.
Section 2C.40	
Figure 2C-11,	Revise to include the use of the Supplemental Warning (W3-9-DE) plaque to draw attention to
Table 2C-1, and	regulatory signs
Section 2C.53-DE	legulatory signs.
	Part 3
Figure 3A-1	Revise figure to include two separate figures: Figure 3A-1A, "Black Contrast Marking Patterns
	on Interstates, Freeways and Expressways" showing white on black ("wet tape") application
	and Figure 3A-1B "Black Contrast Marking Patterns on All Other Roads (NON Interstates,
	Freeways or Expressways)."
	Revise figure to match guidance in the DelDOT Subdivision Manual.
Figure 3B-12A	Revise figure title to "45 mph or More." Add 45 mph option to table.
Figure 3B-12B	Revise figure title to "45 mph or More." Add 45 mph option to table. Change "line lane
	markings" to "lane line markings."
Figure 3B-12C	Revise figure title to "Less than 45 mph." Delete 45 mph option from table.
Figure 3B-13B	Revise figure to extend RPMs through the dotted lines and define RPM spacing through
	dotted line.

Clarify placement of RPMs at lane drops vs. deceleration lanes and spacing of RPMs with 3% figure 3B-13F bottlet striping. Revise 42 m (140 ft) dimension to 30 m (100 ft) and relocate leader to end colid white line. Figure 3B-13F revise figure title. Add note "RPM spacing for dotted 150 mm (6 in) lane lines consisting of 0. m (3 ft) line segments and 2.7 m (9 ft) gaps shall be 7.2 m (24 ft)." Insert space after "144" in Table "A." Figure 3B-13G Revise figure to match guidance in the DelDOT Subdivision Manual. Revise title. Revise figure to extend RPMs through dotted lines. Add note "RPM spacing for dotted 150 mm (6 in) lane lines consisting of 0.9 m (3 ft) line segments and 2.7 m (9 ft) gap shall be 7.2 m (24 ft)." Figure 3B-16A Revise width of median opening to "W 9 m (30 ft)" in Notes 1 and 2. Revise the minimum distance from the stop line to the first approach arrow on the figure on the violeging shall be 7.2 m (24 ft)." Figure 3B-21A Revise minimum distance from the stop line to the first approach arrow on the figure on the violeging shall be 7.2 m (24 ft)." Figure 3B-21A Revise width of median opening to "W 9 m (30 ft)" in Notes 1 and 2. Revise the minimum distance from the stop line to the first approach arrow on the figure on the violeging shall be 7.2 m (24 ft)." Part 6 Appendix Revise figure to extend RPMs through dotted lines. Add note regarding placement of LEFT LANE MUST TURN LEFT sign on undivided roadways. Part 6 Include AHEAD and 1 MILE options in the BRIDGE WORK AHEAD (W5-3-DE) sign to match the sign shown in Case 12. Delete the black-on-white TWO WAY TRAFFIC AHEAD sign and install two Two Way Traffic W6-3) temporary warning signs and the DO NOT PASS (R4-1) sign similar to Typica Application 39 in the Federal MUTCD (see page 6H-83). Revise the DETOUR (M4-10) sign shown in the figure to be black-on-orange. Revise the ROAD CLOSED (R11-2) sign to be black-on-white. Change title to: MOVING DAYTIME OPERATIONS OR SHORT DURATION (1 HOUR OI LESS) STATIONARY - LANE CLOSURE. Add a note stat	
solid white line. Revise figure title. Add note "RPM spacing for dotted 150 mm (6 in) lane lines consisting of 0. m (3 ft) line segments and 2.7 m (9 ft) gaps shall be 7.2 m (24 ft)." Insert space after "144" it Table "A." Figure 3B-13G Revise figure to match guidance in the DeIDOT Subdivision Manual. Revise title. Revise figure to extend RPMs through dotted lines. Add note "RPM spacing for dotted 150 mm (6 in) lane lines consisting of 0.9 m (3 ft) line segments and 2.7 m (9 ft) gap shall be 7.2 m (24 ft)." Figure 3B-16A Revise width of median opening to "W 9 m (30 ft)" in Notes 1 and 2. Revise the minimum distance from the stop line to the first approach arrow on the figure on the fight side of the page from 40 ft to 410 ft. Relocate figure titles to above (rather than below) the von figures. Add note regarding placement of LEFT LANE MUST TURN LEFT sign of undivided roadways. Part 6 Appendix Appendix Include AHEAD and 1 MILE options in the BRIDGE WORK AHEAD (W5-3-DE) sign to match the sign shown in Case 12. Delete the black-on-white TWO WAY TRAFFIC AHEAD sign and install two Two Way Traffic (W6-3) temporary warning signs and the DO NOT PASS (R4-1) sign similar to Typica Application 39 in the Federal MUTCD (see page 6H-83). Case 15 Revise the DETOUR (M4-10) sign shown in the figure to be black-on-orange. Revise the DETOUR (M4-10) sign shown in the figure to be black-on-orange. Revise the OLOSED (R1-12) sign to be black-on-white. Case 20A, Table 6H-1 wo-lane, two-way and multilane roadways. TMA is not required on Vehicle #1; revise figure to the total case is applicable to both two-lane, two-way and multilane roadways. TMA is not required on Vehicle #1; revise figure to the two-lane, two-way and multilane roadways. TMA is not required on Vehicle #1; revise figure to include. Case 20B, Table 6F-1, Section 6F-03. Case 21 Vehicle #6 is not shown; revise figure to include. Figure 6F-3, Table 6F-1, Section 6F-02. Revise to include clarification on vest background to match current standards. Revise	
Figure 3B-13G Figure 3B-13G Figure 3B-13G Figure 3B-13G Figure 3B-13H Figure 3B-13H Figure 3B-13H Figure 3B-13H Figure 3B-13H Figure 3B-16A Fi	leader to end of
Figure 3B-13F m (3 ft) line segments and 2.7 m (9 ft) gaps shall be 7.2 m (24 ft)," Insert space after *144" i Table *A." Figure 3B-13G Revise figure to match guidance in the DelDOT Subdivision Manual. Revise title. Revise figure to extend RPMs through dotted lines. Add note "RPM spacing for dotted 150 mm (6 in) lane lines consisting of 0.9 m (3 ft) line segments and 2.7 m (9 ft) gap shall be 7.2 m (24 ft)." Figure 3B-16A Revise width of median opening to "W 9 m (30 ft)" in Notes 1 and 2. Revise the minimum distance from the stop line to the first approach arrow on the figure on the figure 3B-21A with figures. Add note regarding placement of LEFT LANE MUST TURN LEFT sign of undivided roadways. Part 6 Appendix Include AHEAD and 1 MILE options in the BRIDGE WORK AHEAD (W5-3-DE) sign to match the sign shown in Case 12. Delete the black-on-white TWO WAY TRAFFIC AHEAD sign and install two Two Way Traffic (W6-3) temporary warning signs and the DO NOT PASS (R4-1) sign similar to Typics Application 39 in the Federal MUTCD (see page 6H-83). Revise the DETOUR (M4-10) sign shown in the figure to be black-on-orange. Revise the ROAD CLOSED (R11-2) sign to be black-on-white. Change title to: MOVING DAYTIME OPERATIONS OR SHORT DURATION (1 HOUR DI LESS) STATIONARY - ON SHOULDER. Add a note stating that the case is applicable to bot two-lane, two-way and multilane roadways. TMA is not required on Vehicle #1; revise figure to both two-lane, two-way and multilane roadways. Case 20B, Table 6F-3, Table 6F-1, Section Delete all references to the Weight Limit (R12-2) sign. Figure 6F-3, Table 6F-1, Section Delete all references to the Weight Limit (R12-2) sign. Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. Section 6F-03 Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. Sec	
Figure 3B-13H Revise figure to match guidance in the DelDOT Subdivision Manual. Revise title. Revise figure to extend RPMs through dotted lines. Add note "RPM spacing for dotted 150 mm (6 in) lane lines consisting of 0.9 m (3 ft) line segments and 2.7 m (9 ft) gap shall be 7.2 m (24 ft)." Figure 3B-16A Revise width of median opening to "W 9 m (30 ft)" in Notes 1 and 2. Revise the minimum distance from the stop line to the first approach arrow on the figure on the right side of the page from 40 ft to 410 ft. Relocate figure titles to above (rather than below) the won figures. Add note regarding placement of LEFT LANE MUST TURN LEFT sign or undivided roadways. Part 6 Appendix Revise the minimum distance from the stop line to the first approach arrow on the figure on the right side of the page from 40 ft to 410 ft. Relocate figure titles to above (rather than below) the won figures. Add note regarding placement of LEFT LANE MUST TURN LEFT sign or undivided roadways. Part 6 Appendix Part 6 Appendix Revise the DETOUR (M4-10) sign shown in the BRIDGE WORK AHEAD (W5-3-DE) sign to match the sign shown in Case 12. Delete the bliack-on-white TWO WAY TRAFFIC AHEAD sign and install two Two Way Traffic Application 39 in the Federal MUTCD (see page 681-83). Revise the DETOUR (M4-10) sign shown in the figure to be black-on-orange. Revise the ROAD CLOSED (R11-2) sign to be black-on-white. Change title to: MOVINIS DAYTIME OPERATIONS OR SHORT DURATION (1 HOUR Of LESS) STATIONARY - ON SHOULDER. Add a note stating that the case is applicable to both two-lane, two-way and multilane roadways. Case 21 Change title to: MOVINIS DAYTIME OPERATIONS OR SHORT DURATION (1 HOUR Of LESS) STATIONARY - LANE CLOSURE. Add a note stating that the case is applicable to both two-lane, two-way and multilane roadways. Vehicle #6 is not shown; revise figure to include. Figure 6F-3, Table 6F-1, Section 6F-03 Section 6F-03 Revise to include clarification on vest background to match current standards. Revise text to: "Signs mounted on p	consisting of 0.9
Figure 3B-13H Revise figure to match guidance in the DelDOT Subdivision Manual. Revise title. Revise figure to extend RPMs through dotted lines. Add note "RPM spacing for dotted 150 mm (6 in) lane lines consisting of 0.9 m (3 ft) line segments and 2.7 m (9 ft) gap shall be 7.2 m (24 ft)." Figure 3B-16A Revise width of median opening to "W 9 m (30 ft)" in Notes 1 and 2. Revise the minimum distance from the stop line to the first approach arrow on the figure on the right side of the page from 40 ft to 410 ft. Relocate figure titles to above (rather than below) the won figures. Add note regarding placement of LEFT LANE MUST TURN LEFT sign or undivided roadways. Part 6 Appendix Revise the minimum distance from the stop line to the first approach arrow on the figure on the right side of the page from 40 ft to 410 ft. Relocate figure titles to above (rather than below) the won figures. Add note regarding placement of LEFT LANE MUST TURN LEFT sign or undivided roadways. Part 6 Appendix Part 6 Appendix Revise the DETOUR (M4-10) sign shown in the BRIDGE WORK AHEAD (W5-3-DE) sign to match the sign shown in Case 12. Delete the bliack-on-white TWO WAY TRAFFIC AHEAD sign and install two Two Way Traffic Application 39 in the Federal MUTCD (see page 681-83). Revise the DETOUR (M4-10) sign shown in the figure to be black-on-orange. Revise the ROAD CLOSED (R11-2) sign to be black-on-white. Change title to: MOVINIS DAYTIME OPERATIONS OR SHORT DURATION (1 HOUR Of LESS) STATIONARY - ON SHOULDER. Add a note stating that the case is applicable to both two-lane, two-way and multilane roadways. Case 21 Change title to: MOVINIS DAYTIME OPERATIONS OR SHORT DURATION (1 HOUR Of LESS) STATIONARY - LANE CLOSURE. Add a note stating that the case is applicable to both two-lane, two-way and multilane roadways. Vehicle #6 is not shown; revise figure to include. Figure 6F-3, Table 6F-1, Section 6F-03 Section 6F-03 Revise to include clarification on vest background to match current standards. Revise text to: "Signs mounted on p	ce after "144" in
Figure 3B-13G Revise figure to match guidance in the DelDOT Subdivision Manual. Revise title. Revise figure to extend RPMs through dotted lines. Add note "RPM spacing for dotted 150 mm (6 in) lane lines consisting of 0.9 m (3 ft) lines segments and 2.7 m (9 ft) gap shall be 7.2 m (24 ft)." Figure 3B-16A Revise width of median opening to "W 9 m (30 ft)" in Notes 1 and 2. Revise the minimum distance from the stop line to the first approach arrow on the figure on the right side of the page from 40 ft to 410 ft. Relocate figure titles to above (rather than below) the won figures. Add note regarding placement of LEFT LANE MUST TURN LEFT sign on undivided roadways. Part 6 Appendix Include AHEAD and 1 MILE options in the BRIDGE WORK AHEAD (W5-3-DE) sign to match the sign shown in Case 12. Delete the black-on-white TWO WAY TRAFFIC AHEAD sign and install two Two Way Traffic Application 39 in the Federal MUTCD (see page 6H-83). Case 15 Revise the DETOUR (M4-10) sign shown in the figure to be black-on-orrange. Revise the DETOUR (M4-10) sign shown in the figure to be black-on-orrange. Revise the CLOSED (R1-12) sign to be black-on-white. Change title to: MOVING DAYTIME OPERATIONS OR SHORT DURATION (1 HOUR OI two-lane, two-way and multilane roadways. TMA is not required on Vehicle #1; revise figure to both two-lane, two-way and multilane roadways. TMA is not required on Vehicle #1; revise figure to both two-lane, two-way and multilane roadways. Case 20B, Table 6F-1, Section 6F-3, Table 6F-1, Section 6F-3, Table 6F-1, Section 6F-3, Table 6F-1, Section 6F-30 Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. Section 6F-03 Revise to include clarification on vest background to match current standards. Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. Make this a standard	
Figure 3B-16A Figure 3B-16A Figure 3B-16A Figure 3B-21A Fi	
Figure 3B-13H dotted 150 mm (6 in) Iane lines consisting of 0.9 m (3 ft) line segments and 2.7 m (9 ft) gap shall be 7.2 m (24 ft)." Figure 3B-16A Revise width of median opening to "W 9 m (30 ft)" in Notes 1 and 2. Revise the minimum distance from the stop line to the first approach arrow on the figure on the right side of the page from 40 ft to 410 ft. Relocate figure titles to above (rather than below) the two figures. Add note regarding placement of LEFT LANE MUST TURN LEFT sign of undivided roadways. Part 6 Appendix Include AHEAD and 1 MILE options in the BRIDGE WORK AHEAD (W5-3-DE) sign to match the sign shown in Case 12. Delete the black-on-white TWO WAY TRAFFIC AHEAD sign and install two Two Way Traffication 39 in the Federal MUTCD (see page 6H-83). Case 15 Revise the DETOUR (M4-10) sign shown in the figure to be black-on-orange. Revise the ROAD CLOSED (R11-2) sign to be black-on-white. Change title to: MOVING DAYTIME OPERATIONS OR SHORT DURATION (1 HOUR Of Case 20A, Table 12 Kmo-way and multilane roadways. TMA is not required on Vehicle #1; revise figure to both two-lane, two-way and multilane roadways. Case 20B, Table 6F-1, Section 6F-10 Figure 6F-3, Table 6F-1, Section 6F-03 Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. (Make this a standard and delete the double negative). Revise to include opportation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. (Make this a standard and delete the double negative). Revise to include opportation services figure to include. Section 6F-03 Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. (Make this a standard and delete the double negative). Revise to include option: "If utilit conflicts or concrete sidewalks/medians prevent the installation of permanent signs i	PM spacing for
shall be 7.2 m (24 ft)." Figure 3B-16A Revise width of median opening to "W 9 m (30 ft)" in Notes 1 and 2. Revise the minimum distance from the stop line to the first approach arrow on the figure on the right side of the page from 40 ft to 410 ft. Relocate figure titles to above (rather than below) the working figures. Add note regarding placement of LEFT LANE MUST TURN LEFT sign of undivided roadways. Part 6 Appendix Include AHEAD and 1 MILE options in the BRIDGE WORK AHEAD (W5-3-DE) sign to match the sign shown in Case 12. Delete the black-on-white TWO WAY TRAFFIC AHEAD sign and install two Two Way Traffic (W6-3) temporary warning signs and the DO NOT PASS (R4-1) sign similar to Typice Application 39 in the Federal MUTCD (see page 6H-83). Case 15 Revise the DETOUR (M4-10) sign shown in the figure to be black-on-orange. Revise the ROAD CLOSED (R11-2) sign to be black-on-white. Change title to: MOVING DAYTIME OPERATIONS OR SHORT DURATION (1 HOUR Of the delete TMA. Case 208, Table 6H-1 Case 208, Table 6H-1 Garge itile to: MOVING DAYTIME OPERATIONS OR SHORT DURATION (1 HOUR Of the delete TMA. Case 21 Vehicle #6 is not shown; revise figure to include. Figure 6F-3, Table 6F-1, Section 6F-10 Section 6E-02 Revise to include clarification on vest background to match current standards. Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. Make this a standard and delete the double negative). Revise to include option: "If utilit conflicts or concrete sidewalks/medians prevent the installation of permanent signs in the appropriate location, portable sign supports may be used." Delete "Option: Type III Barricades used at a road closure may be placed completely across or oadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure shall be placed completely across or oadway or from curb to curb." This statement conflicts with the standa	
Figure 3B-16A Revise width of median opening to "W 9 m (30 ft)" in Notes 1 and 2. Revise the minimum distance from the stop line to the first approach arrow on the figure on the right side of the page from 40 ft to 410 ft. Relocate figure titles to above (rather than below) the violation of violat	<i>r</i> III (5 II) gaps
Revise the minimum distance from the stop line to the first approach arrow on the figure on the right side of the page from 40 ft to 410 ft. Relocate figure titles to above (rather than below) the high side of the page from 40 ft to 410 ft. Relocate figure titles to above (rather than below) the high side of the page from 40 ft to 410 ft. Relocate figure titles to above (rather than below) the highest side of the page from 40 ft to 410 ft. Relocate figure titles to above (rather than below) the highest side of the page form 40 ft to 410 ft. Relocate figure titles to above (rather than below) the highest side of the page form 40 ft. Relocate figure titles to above (rather than below) the highest side of the page form 40 ft. Relocate figure titles to above (rather than below) the highest side of the page form 40 ft. Relocate figure titles to above (rather than below) the house highest side of the page form 40 ft. Relocate figure titles to above (rather than below) the highest side of the page form 40 ft. Relocate figure titles to above (rather than below) the highest side of the page form 40 ft. Relocate figure titles to above (rather than below) the highest side of the page form 40 ft. Relocate figure titles to above (rather than below) than the page figure titles to above (rather than below) than the page figure titles to above (rather than below) that the sign sign to the BRIDGE work AHEAD (MS-3-DE) sign to delete title to the Way Traffic Engine of the page figure to include. Revise the DETOUR (MA-10) sign shown in the figure to be black-on-orange. Revise the page form 40 ft. Accept the page form	
right side of the page from 40 ft to 410 ft. Relocate figure titles to above (rather than below) the two figures. Add note regarding placement of LEFT LANE MUST TURN LEFT sign of undivided roadways. Part 6 Appendix Appendix Part 6 Include AHEAD and 1 MILE options in the BRIDGE WORK AHEAD (W5-3-DE) sign to match the sign shown in Case 12. Delete the black-on-white TWO WAY TRAFFIC AHEAD sign and install two Two Way Traffic (W6-3) temporary warning signs and the DO NOT PASS (R4-1) sign similar to Typica Application 39 in the Federal MUTCD (see page 6H-83). Case 15 Case 15 Case 15 Case 15 Case 20A, Table LESS) STATIONARY - ON SHOULDER. Add a note stating that the case is applicable to bot two-lane, two-way and multilane roadways. TMA is not required on Vehicle #1; revise figure to delete TMA. Case 20B, Table Case 21 Case 21 Case 21 Figure 6F-3, Table 6F-1, Section 6F-10 Section 6E-02 Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. Make this a standard and delete the double negative). Revise to include option: "If utilit conflicts or concrete sidewalks/medians prevent the installation of permanent signs in the appropriate location, portable sign supports may be used." Delete "Option: Type III Barricades used at road closure may be placed completely across oadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure shall be placed completely across a roadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure shall be placed completely across a roadway or from curb to curb." (se page 6F-36) Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	the figure on the
Part 6 Appendix Include AHEAD and 1 MILE options in the BRIDGE WORK AHEAD (W5-3-DE) sign to mate the sign shown in Case 12. Delete the black-on-white TWO WAY TRAFFIC AHEAD sign and install two Two Way Traffic (W6-3) temporary warning signs and the DO NOT PASS (R4-1) sign similar to Typice Application 39 in the Federal MUTCD (see page 6H-83). Case 15 Revise the DETOUR (M4-10) sign shown in the figure to be black-on-orange. Revise the ROAD CLOSED (R11-2) sign to be black-on-white. Change title to: MOVING DAYTIME OPERATIONS OR SHORT DURATION (1 HOUR OI LESS) STATIONARY - ON SHOULDER. Add a note stating that the case is applicable to both wo-lane, two-way and multilane roadways. TMA is not required on Vehicle #1; revise figure to delete TMA. Case 20B, Table 6H-1 Change title to: MOVING DAYTIME OPERATIONS OR SHORT DURATION (1 HOUR OI LESS) STATIONARY - LANE CLOSURE. Add a note stating that the case is applicable to both two-lane, two-way and multilane roadways. Vehicle #6 is not shown; revise figure to include. Figure 6F-3, Table 6F-1, Section 6F.10 Section 6E.02 Revise to include clarification on vest background to match current standards. Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. (Make this a standard and delete the double negative). Revise to include option: "If utilit conflicts or concrete sidewalks/medians prevent the installation of permanent signs in the page 6F-36) Table 6F-1 and Appendix Revise text to: "Signs mounted on portable supports and be test and and appendix Appendix Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	-
Appendix Appendix Appendix Appendix Appendix Appendix Appendix Case 12 Delete the black-on-white TWO WAY TRAFFIC AHEAD sign and install two Two Way Traffic (W6-3) temporary warning signs and the DO NOT PASS (R4-1) sign similar to Typica Application 39 in the Federal MUTCD (see page 6H-83). Revise the DETOUR (M4-10) sign shown in the figure to be black-on-orange. Revise the ROAD CLOSED (R11-2) sign to be black-on-white. Case 20A, Table LESS) STATIONARY - ON SHOULDER. Add a note stating that the case is applicable to both two-lane, two-way and multilane roadways. TMA is not required on Vehicle #1; revise figure to delete TMA. Case 20B, Table 6H-1 Case 20B, Table 6H-1 Case 21 Figure 6F-3, Table 6F-1, Section 6F.10 Section 6E.02 Revise to include clarification on vest background to match current standards. Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. Section 6F.03 Section 6F.03 Section 6F.63 Section 6F.63 Section 6F.63 Revise text to: "Type III Barricades used at a road closure may be placed completely across a roadway or from curb to curb." (se page 6F-36) Table 6F-1 and Appendix Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	,
Appendix Include AHEAD and 1 MILE options in the BRIDGE WORK AHEAD (W5-3-DE) sign to match the sign shown in Case 12. Delete the black-on-white TWO WAY TRAFFIC AHEAD sign and install two Two Way Traffication 39 in the Federal MUTCD (see page 6H-83). Case 15 Case 15 Revise the DETOUR (M4-10) sign shown in the figure to be black-on-orange. Revise the ROAD CLOSED (R11-2) sign to be black-on-white. Change title to: MOVING DAYTIME OPERATIONS OR SHORT DURATION (1 HOUR Of LESS) STATIONARY - ON SHOULDER. Add a note stating that the case is applicable to both two-lane, two-way and multilane roadways. TMA is not required on Vehicle #1; revise figure to both two-lane, two-way and multilane roadways. Case 20B, Table 6H-1 Change title to: MOVING DAYTIME OPERATIONS OR SHORT DURATION (1 HOUR Of LESS) STATIONARY - LANE CLOSURE. Add a note stating that the case is applicable to both two-lane, two-way and multilane roadways. Case 21 Vehicle #6 is not shown; revise figure to include. Figure 6F-3, Table 6F-1, Section 6F.10 Figure 6F-3, Table 6F-10 Section 6E.02 Revise to include clarification on vest background to match current standards. Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. Section 6F.03 Make this a standard and delete the double negative). Revise to include option: "If utilit conflicts or concrete sidewalks/medians prevent the installation of permanent signs in the appropriate location, portable sign supports may be used." Delete "Option: Type III Barricades used at a road closure may be placed completely across oadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure shall be placed completely across a roadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure shall be placed completely across a roadway or from curb to curb." (se Page 6F-36) Table 6F-1 and Append	LEFT sign on
Appendix Appendix Include AHEAD and 1 MILE options in the BRIDGE WORK AHEAD (W5-3-DE) sign to match the sign shown in Case 12. Delete the black-on-white TWO WAY TRAFFIC AHEAD sign and install two Two Way Traffic (W6-3) temporary warning signs and the DO NOT PASS (R4-1) sign similar to Typice Application 39 in the Federal MUTCD (see page 6H-83). Revise the DETOUR (M4-10) sign shown in the figure to be black-on-orange. Revise the ROAD CLOSED (R11-2) sign to be black-on-white. Change title to: MOVING DAYTIME OPERATIONS OR SHORT DURATION (1 HOUR OF GH-1)	
the sign shown in Case 12. Delete the black-on-white TWO WAY TRAFFIC AHEAD sign and install two Two Way Traffic (W6-3) temporary warning signs and the DO NOT PASS (R4-1) sign similar to Typica Application 39 in the Federal MUTCD (see page 6H-83). Case 15 Revise the DETOUR (M4-10) sign shown in the figure to be black-on-orange. Revise the ROAD CLOSED (R11-2) sign to be black-on-white. Change title to: MOVING DAYTIME OPERATIONS OR SHORT DURATION (1 HOUR OI to two-lane, two-way and multilane roadways. TMA is not required on Vehicle #1; revise figure to delete TMA. Case 20B, Table 6H-1 Case 21 Figure 6F-3, Table 6F-1, Section 6F.10 Figure 6F-3, Table 6F-1. Section 6E.02 Revise to include clarification on vest background to match current standards. Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. Section 6F.03 Section 6F.63 Section 6F.63 Revise to include clatification on vest background to match current standards. Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. Make this a standard and delete the double negative). Revise to include option: "If utilit conflicts or concrete sidewalks/medians prevent the installation of permanent signs in the appropriate location, portable sign supports may be used." Delete "Option: Type III Barricades used at a road closure may be placed completely across oadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure may be placed completely across oadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure may be placed completely across oadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure may be placed completely across oadway or from curb to curb." Thi	
Case 12 Delete the black-on-white TWO WAY TRAFFIC AHEAD sign and install two Two Way Traffic (W6-3) temporary warning signs and the DO NOT PASS (R4-1) sign similar to Typica Application 39 in the Federal MUTCD (see page 6H-83). Revise the DETOUR (M4-10) sign shown in the figure to be black-on-orange. Revise the ROAD CLOSED (R11-2) sign to be black-on-white. Change title to: MOVING DAYTIME OPERATIONS OR SHORT DURATION (1 HOUR Of the case is applicable to bot two-lane, two-way and multilane roadways. TMA is not required on Vehicle #1; revise figure to delete TMA. Case 20B, Table 6H-1 Case 20B, Table 6H-1 Case 21 Case 21 Figure 6F-3, Table 6F-1, Section 6F.10 Section 6E.02 Revise to include clarification on vest background to match current standards. Revise to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. Section 6F.03 Section 6F.63 Section 6F.63 Section 6F.63 Revise to include clarin, portable sign supports may be used." Delete "Option: Type III Barricades used at a road closure may be placed completely across. oadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure shall be placed completely across a roadway or from curb to curb." (se page 6F-36) Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	E) sign to match
Case 12 (W6-3) temporary warning signs and the DO NOT PASS (R4-1) sign similar to Typica Application 39 in the Federal MUTCD (see page 6H-83). Revise the DETOUR (M4-10) sign shown in the figure to be black-on-orange. Revise th ROAD CLOSED (R11-2) sign to be black-on-white. Change title to: MOVING DAYTIME OPERATIONS OR SHORT DURATION (1 HOUR OF 6H-1) (LESS) STATIONARY - ON SHOULDER. Add a note stating that the case is applicable to bot two-lane, two-way and multilane roadways. TMA is not required on Vehicle #1; revise figure to delete TMA. Case 20B, Table (Change title to: MOVING DAYTIME OPERATIONS OR SHORT DURATION (1 HOUR OF 6H-1) (LESS) STATIONARY - LANE CLOSURE. Add a note stating that the case is applicable to both two-lane, two-way and multilane roadways. Case 21 Vehicle #6 is not shown; revise figure to include. Figure 6F-3, Table 6F-1, Section 6F.10 Section 6E.02 Revise to include clarification on vest background to match current standards. Revise to include clarification on vest background to match current standards. Revise to include clarification on vest background to match current standards. Revise to include clarification on vest background to match current standards. Revise to include clarification on vest background to match current standards. Revise to include clarification on vest background to match current standards. Revise to include clarification on vest background to match current standards. Revise to include clarification on vest background to match current standards. Revise to include clarification on vest background to match current standards. Revise to include clarification on vest background to match current standards. Revise to include clarification on vest background to match current standards. Revise to include clarification on vest background to match current standards. Revise to include clarification on vest background to match current standards. Revise to include clarification on vest background to match current standards. Revise to include clarification on ve	
Application 39 in the Federal MUTCD (see page 6H-83). Case 15 Revise the DETOUR (M4-10) sign shown in the figure to be black-on-orange. Revise the NOAD CLOSED (R11-2) sign to be black-on-white. Change title to: MOVING DAYTIME OPERATIONS OR SHORT DURATION (1 HOUR OF 6H-1) two-lane, two-way and multilane roadways. TMA is not required on Vehicle #1; revise figure to delete TMA. Case 20B, Table 6H-1 Case 20B, Table 6F-3, Table 6F-1, Section 6F.10 Section 6F.02 Revise to include clarification on vest background to match current standards. Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. (Make this a standard and delete the double negative). Revise to include option: "If utilit conflicts or concrete sidewalks/medians prevent the installation of permanent signs in the appropriate location, portable sign supports may be used." Delete "Option: Type III Barricades used at a road closure may be placed completely across roadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure may be placed completely across a roadway or from curb to curb." (se Page 6F-36) Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	Гwo Way Traffic
Application 39 in the Federal MUTCD (see page 6H-83). Case 15 Revise the DETOUR (M4-10) sign shown in the figure to be black-on-orange. Revise the NOAD CLOSED (R11-2) sign to be black-on-white. Change title to: MOVING DAYTIME OPERATIONS OR SHORT DURATION (1 HOUR OF 6H-1) two-lane, two-way and multilane roadways. TMA is not required on Vehicle #1; revise figure to delete TMA. Case 20B, Table 6H-1 Case 20B, Table 6F-3, Table 6F-1, Section 6F.10 Section 6F.02 Revise to include clarification on vest background to match current standards. Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. (Make this a standard and delete the double negative). Revise to include option: "If utilit conflicts or concrete sidewalks/medians prevent the installation of permanent signs in the appropriate location, portable sign supports may be used." Delete "Option: Type III Barricades used at a road closure may be placed completely across roadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure may be placed completely across a roadway or from curb to curb." (se Page 6F-36) Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	nilar to Typical
Case 15 Revise the DETOUR (M4-10) sign shown in the figure to be black-on-orange. Revise th ROAD CLOSED (R11-2) sign to be black-on-white. Change title to: MOVING DAYTIME OPERATIONS OR SHORT DURATION (1 HOUR OF LESS) STATIONARY - ON SHOULDER. Add a note stating that the case is applicable to both two-lane, two-way and multilane roadways. TMA is not required on Vehicle #1; revise figure to delete TMA. Case 20B, Table 6H-1 Case 20B, Table 6H-1 Oth two-lane, two-way and multilane roadways. Case 21 Vehicle #6 is not shown; revise figure to include. Figure 6F-3, Table 6F-1, Section 6F-10 Figure 6F-3, Table 6F-1, Section 6F-10 Section 6E.02 Revise to include clarification on vest background to match current standards. Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. Make this a standard and delete the double negative). Revise to include option: "If utilit conflicts or concrete sidewalks/medians prevent the installation of permanent signs in the appropriate location, portable sign supports may be used." Delete "Option: Type III Barricades used at a road closure may be placed completely across roadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure shall be placed completely across a roadway or from curb to curb." (se Page 6F-3a) Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	7.
Case 20A, Table 6H-1 Case 20B, Table 6H-1 Case 21 Case	nge. Revise the
Case 20A, Table 6H-1 Case 20B, Table 6H-1 Case 21 Change title to: MOVING DAYTIME OPERATIONS OR SHORT DURATION (1 HOUR OF DAYTIME OPERATIO	
Case 20A, Table 6H-1 two-lane, two-way and multilane roadways. TMA is not required on Vehicle #1; revise figure to delete TMA. Case 20B, Table 6H-1 Change title to: MOVING DAYTIME OPERATIONS OR SHORT DURATION (1 HOUR OF LESS) STATIONARY - LANE CLOSURE. Add a note stating that the case is applicable to both two-lane, two-way and multilane roadways. Case 21 Vehicle #6 is not shown; revise figure to include. Figure 6F-3, Table 6F-1, Section 6F.10 Delete all references to the Weight Limit (R12-2) sign. 6F-10 Section 6E.02 Revise to include clarification on vest background to match current standards. Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. Section 6F.03 Make this a standard and delete the double negative). Revise to include option: "If utilit conflicts or concrete sidewalks/medians prevent the installation of permanent signs in th appropriate location, portable sign supports may be used." Delete "Option: Type III Barricades used at a road closure may be placed completely across roadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure may be placed completely across roadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure shall be placed completely across a roadway or from curb to curb." (se Page 6F-36) Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	N (1 HOUR OR
two-lane, two-way and multilane roadways. TMA is not required on Vehicle #1; revise figure to delete TMA. Case 20B, Table 6H-1 Case 21 Case 21 Case 21 Vehicle #6 is not shown; revise figure to include. Figure 6F-3, Table 6F-1, Section 6F-10 Figure 6F-3, Table 6F-1, Section 6F.10 Section 6E.02 Revise to include clarification on vest background to match current standards. Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. (Make this a standard and delete the double negative). Revise to include option: "If utilit conflicts or concrete sidewalks/medians prevent the installation of permanent signs in the appropriate location, portable sign supports may be used." Delete "Option: Type III Barricades used at a road closure may be placed completely across roadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure shall be placed completely across a roadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure shall be placed completely across a roadway or from curb to curb." (se Page 6F-36) Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	•
delete TMA. Case 20B, Table 6H-1 Case 20B, Table 6H-1 Case 21 Case 21 Figure 6F-3, Table 6F-1, Section 6F.10 Section 6E.02 Revise to include clarification on vest background to match current standards. Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. Section 6F.03 Section 6F.03 Section 6F.03 Section 6F.03 Section 6F.03 Revise to include clarification on vest background to match current standards. Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. (Make this a standard and delete the double negative). Revise to include option: "If utilit conflicts or concrete sidewalks/medians prevent the installation of permanent signs in the appropriate location, portable sign supports may be used." Delete "Option: Type III Barricades used at a road closure may be placed completely across. roadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure shall be placed completely across a roadway or from curb to curb." (se Page 6F-36) Table 6F-1 and Appendix Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	•
Case 20B, Table 6H-1 Case 21 Case 3 Case 21 Case 3 Case 21 Case 3 C	, revise ligure to
Case 20B, Table 6H-1 both two-lane, two-way and multilane roadways. Case 21 Vehicle #6 is not shown; revise figure to include. Figure 6F-3, Table 6F-1, Section 6F.10 Figure 6F-3, Table 6F-1, Section 6F.10 Section 6E.02 Revise to include clarification on vest background to match current standards. Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. Section 6F.03 Section 6F.03 Make this a standard and delete the double negative). Revise to include option: "If utilit conflicts or concrete sidewalks/medians prevent the installation of permanent signs in th appropriate location, portable sign supports may be used." Delete "Option: Type III Barricades used at a road closure may be placed completely across roadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure shall be placed completely across a roadway or from curb to curb." (se Page 6F-36) Table 6F-1 and Appendix Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	N (4 HOUD OD
Case 21 Vehicle #6 is not shown; revise figure to include. Figure 6F-3, Table 6F-1, Section 6F.10 Section 6E.02 Revise to include clarification on vest background to match current standards. Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. (Make this a standard and delete the double negative). Revise to include option: "If utilit conflicts or concrete sidewalks/medians prevent the installation of permanent signs in the appropriate location, portable sign supports may be used." Delete "Option: Type III Barricades used at a road closure may be placed completely across roadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure shall be placed completely across a roadway or from curb to curb." (se Page 6F-36) Table 6F-1 and Appendix Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	•
Case 21 Vehicle #6 is not shown; revise figure to include. Figure 6F-3, Table 6F-1, Section 6F.10 Figure 6F-3, Table 6F-1, Section 6F.10 Delete all references to the Weight Limit (R12-2) sign. 6F.10 Section 6E.02 Revise to include clarification on vest background to match current standards. Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. Section 6F.03 (Make this a standard and delete the double negative). Revise to include option: "If utilit conflicts or concrete sidewalks/medians prevent the installation of permanent signs in th appropriate location, portable sign supports may be used." Delete "Option: Type III Barricades used at a road closure may be placed completely across roadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure shall be placed completely across a roadway or from curb to curb." (se Page 6F-36) Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	is applicable to
Figure 6F-3, Table 6F-1, Section 6F.10 Figure 6F-3, Table 6F-1, Section 6F.10 Figure 6F-3, Table 6F-1, Section 6F.10 Section 6E.02 Revise to include clarification on vest background to match current standards. Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. (Make this a standard and delete the double negative). Revise to include option: "If utilit conflicts or concrete sidewalks/medians prevent the installation of permanent signs in th appropriate location, portable sign supports may be used." Delete "Option: Type III Barricades used at a road closure may be placed completely across roadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure shall be placed completely across a roadway or from curb to curb." (se Page 6F-36) Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	
6F-1, Section 6F-10 Figure 6F-3, Table 6F-1, Section 6F.10 Delete all references to the Weight Limit (with Symbols) R12-5 sign; replace with R12-5-DE. 6F-1, Section 6F.10 Section 6E.02 Revise to include clarification on vest background to match current standards. Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. (Make this a standard and delete the double negative). Revise to include option: "If utilit conflicts or concrete sidewalks/medians prevent the installation of permanent signs in th appropriate location, portable sign supports may be used." Delete "Option: Type III Barricades used at a road closure may be placed completely across roadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure shall be placed completely across a roadway or from curb to curb." (se Page 6F-36) Table 6F-1 and Appendix Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	
Figure 6F-3, Table 6F-1, Section 6F-10 Section 6E.02 Revise to include clarification on vest background to match current standards. Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. Section 6F.03 (Make this a standard and delete the double negative). Revise to include option: "If utilit conflicts or concrete sidewalks/medians prevent the installation of permanent signs in th appropriate location, portable sign supports may be used." Delete "Option: Type III Barricades used at a road closure may be placed completely across roadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure shall be placed completely across a roadway or from curb to curb." (se Page 6F-36) Table 6F-1 and Appendix Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	
Figure 6F-3, Table 6F-1, Section 6F.10 Section 6E.02 Revise to include clarification on vest background to match current standards. Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. (Make this a standard and delete the double negative). Revise to include option: "If utilit conflicts or concrete sidewalks/medians prevent the installation of permanent signs in the appropriate location, portable sign supports may be used." Section 6F.63 Section 6F.63 Delete "Option: Type III Barricades used at a road closure may be placed completely across roadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure shall be placed completely across a roadway or from curb to curb." (se Page 6F-36) Table 6F-1 and Appendix Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	
6F-1, Section 6F.10 Section 6E.02 Revise to include clarification on vest background to match current standards. Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. (Make this a standard and delete the double negative). Revise to include option: "If utilit conflicts or concrete sidewalks/medians prevent the installation of permanent signs in the appropriate location, portable sign supports may be used." Delete "Option: Type III Barricades used at a road closure may be placed completely across roadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure shall be placed completely across a roadway or from curb to curb." (se Page 6F-36) Table 6F-1 and Appendix Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	
Section 6E.02 Revise to include clarification on vest background to match current standards. Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. (Make this a standard and delete the double negative). Revise to include option: "If utilit conflicts or concrete sidewalks/medians prevent the installation of permanent signs in the appropriate location, portable sign supports may be used." Delete "Option: Type III Barricades used at a road closure may be placed completely across roadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure shall be placed completely across a roadway or from curb to curb." (se Page 6F-36) Table 6F-1 and Appendix Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	
Section 6E.02 Revise to include clarification on vest background to match current standards. Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. (Make this a standard and delete the double negative). Revise to include option: "If utilit conflicts or concrete sidewalks/medians prevent the installation of permanent signs in the appropriate location, portable sign supports may be used." Delete "Option: Type III Barricades used at a road closure may be placed completely across roadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure shall be placed completely across a roadway or from curb to curb." (se Page 6F-36) Table 6F-1 and Appendix Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	ith R12-5-DE.
Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. (Make this a standard and delete the double negative). Revise to include option: "If utilit conflicts or concrete sidewalks/medians prevent the installation of permanent signs in the appropriate location, portable sign supports may be used." Delete "Option: Type III Barricades used at a road closure may be placed completely across roadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure shall be placed completely across a roadway or from curb to curb." (se Page 6F-36) Table 6F-1 and Appendix Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	
Revise text to: "Signs mounted on portable supports shall not be used for operation exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. (Make this a standard and delete the double negative). Revise to include option: "If utilit conflicts or concrete sidewalks/medians prevent the installation of permanent signs in the appropriate location, portable sign supports may be used." Delete "Option: Type III Barricades used at a road closure may be placed completely across roadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure shall be placed completely across a roadway or from curb to curb." (se Page 6F-36) Table 6F-1 and Appendix Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	
Section 6F.03 Exceeding 24 hours in duration, unless approved by the Chief Traffic Engineer or designee. (Make this a standard and delete the double negative). Revise to include option: "If utilit conflicts or concrete sidewalks/medians prevent the installation of permanent signs in the appropriate location, portable sign supports may be used." Delete "Option: Type III Barricades used at a road closure may be placed completely across roadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure shall be placed completely across a roadway or from curb to curb." (se Page 6F-36) Table 6F-1 and Appendix Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	
Section 6F.03 (Make this a standard and delete the double negative). Revise to include option: "If utilit conflicts or concrete sidewalks/medians prevent the installation of permanent signs in the appropriate location, portable sign supports may be used." Delete "Option: Type III Barricades used at a road closure may be placed completely across a roadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure shall be placed completely across a roadway or from curb to curb." (se Page 6F-36) Table 6F-1 and Appendix Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	•
conflicts or concrete sidewalks/medians prevent the installation of permanent signs in the appropriate location, portable sign supports may be used." Delete "Option: Type III Barricades used at a road closure may be placed completely across roadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure shall be placed completely across a roadway or from curb to curb." (se Page 6F-36) Table 6F-1 and Appendix Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	_
Section 6F.63 Table 6F-1 and Appendix Appropriate location, portable sign supports may be used." Delete "Option: Type III Barricades used at a road closure may be placed completely across roadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure shall be placed completely across a roadway or from curb to curb." (see Page 6F-36) Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	•
Section 6F.63 Delete "Option: Type III Barricades used at a road closure may be placed completely across roadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure shall be placed completely across a roadway or from curb to curb." (se Page 6F-36) Table 6F-1 and Appendix Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	ATT SIGNS III IIIO
Section 6F.63 roadway or from curb to curb." This statement conflicts with the standard "Type III Barricade used at road closure shall be placed completely across a roadway or from curb to curb." (se Page 6F-36) Table 6F-1 and Appendix Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	plotoly across s
used at road closure shall be placed completely across a roadway or from curb to curb." (se Page 6F-36) Table 6F-1 and Appendix Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	
used at road closure shall be placed completely across a roadway or from curb to curb." (se Page 6F-36) Table 6F-1 and Appendix Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	
Table 6F-1 and Appendix Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	rb to curb." (see
Revise the KEEP LEFT (R4-8-DE) sign to delete the RIGHT option.	
Appendix	
II Lobio CL 4 and 1	
Table 6F-1 and Insert the KEEP RIGHT (R4-7-DE) sign.	
Appendix	
Insert the KEEP RI(4H1 (R4-7-1)E) sign	

Table 6F-1 and Appendix Insert LANE CLOSED (W9-3-DE2) temporary warning sign.	
---	--

Note: Revisions to the Table of Contents will be made to accommodate proposed revisions

Public Comment Period

The Department will take written comments on the draft changes to the Delaware MUTCD from July 1, 2008 through July 31, 2008.

Copies of the Draft Delaware MUTCD Revisions to Parts 2, 3, and 6 can be obtained by reviewing or downloading a PDF copy at the following web address: http://regulations.delaware.gov/july2008/proposed/MUTCD236.

Questions or comments regarding this document should be directed to:

Donald Weber, P.E.

Assistant Director of Transportation Engineering Division of Transportation Solutions

Delaware Department of Transportation

169 Brick Store Landing Road

Smyrna, DE 19977

(302) 659-2002 (telephone)

(302) 653-2859 (fax)

don.weber@state.de.us

*Please Note: Due to the size of the proposed regulation, the DelDOT Manual on Uniform Traffic Control Devices, Parts 2, 3 and 6, is not being published here. A PDF version is available at the website listed below:

http://regulations.delaware.gov/register/july2008/proposed/MUTCD236.pdf MUTCD236

12 DE Reg. 56 (07/01/08) (Prop.)